

DOUBLE-SIDED ADHESIVE TAPE

IPMT PLATE MOUNTING TAPE

Engineered for mounting plates in flexographic and letterpress printing — even impression across the plate, a firm hold at press speed, and clean release after the run.



WHY CHOOSE IPMT



Even impression

The cushioned carrier evens out press impression for clean, consistent dots.



Holds at speed

High-grab adhesive keeps plate edges locked down for the whole run.



Clean release

Peels off plate and cylinder with no residue and no plate damage.



Bubble-free mounting

The corrugated liner leaves air-escape channels in the adhesive — bubbles press out, not trapped.

Part of the Fortis adhesive tape range — splicing · process · tear · sealing · repulpable · core starting

FORTIS INDUSTRIAL SDN BHD

201001020459 (904229-V)

F-2-16 Suite 11, IOI Boulevard, Jalan Kenari 5,
Bandar Puchong Jaya, 47170 Puchong, Selangor.

(603) 8073 2667 · (603) 8073 2688

all@fortisindustrial.com.my

www.fortisindustrial.com.my

INSTALLATION STEPS

CLEAN






Plate cleaning

MOUNT



Tape application



Peel the liner





Plate removal



Cylinder cleaning



Squeegee the liner





Plate mounting



Tape removal

Corrugated liner — no trapped air. Air escapes through the liner's channels as you squeegee. After mounting, press the plate down with a rubber roller.



Before use, clean with IPA. Wipe the plate back and cylinder with isopropyl alcohol and let dry completely.

TWO WAYS TO MOUNT

A

TAPE THE PLATE FIRST

Apply tape to the back of the plate, then mount the plate on the cylinder.

B

TAPE THE CYLINDER FIRST

Wrap tape around the cylinder, then lay the plate on. Never overlap the joint.