



tesa® 50948

Product Information



tesa® 50948

Product Description

tesa® 50948 is a double-sided splicing tape consisting of a black PET backing and a very high tack contact adhesive.

It is particularly suitable for splicing film materials, with a high slip content in converting, laminating, and printing processes.

Application Fields

Customer benefits

- Secure splicing performance due to excellent wetting properties
- Well suited for a wide variety of film materials, e.g. high slip films, recycled films and non-wovens
- Runs at high speeds
- Reduces waste and improves the carbon footprint

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PET	• Color	black
• Type of adhesive	synthetic rubber	• Color of liner	white with tesa logo
• Type of liner	paper	• Thickness of film	12 µm
• Total thickness	95 µm		

Properties/Performance Values

• Shelf life time (packed) < 25°C	18 months	• Tack	very good
• Static shear resistance	good		

Adhesion to Values

• PE (initial)	3.3 N/mm
----------------	----------



tesa® 50948

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50948>