



tesa® 51334

Product Information



Paper-based tear tape

Product Description

Recyclable, white paper-based tear tape for easy opening applications of paper-based packaging solutions, such as lightweight packaging boxes or envelopes.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- Strong paper backing and high adhesion on board materials for reliable and quick opening of various packagings
- Homogenous visual appearance within final packaging
- Product design helps to achieve higher content of single source packaging material
- Smooth unwinding and proven processability on market standard tape applicators

Application Fields

- Designed for a secure and reliable opening performance of lightweight packagings made of corrugated board, cardboard or paper
- Recommended for automatic production

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--|-------|--------------------|------------------|
| • Backing | Paper | • Type of adhesive | synthetic rubber |
| • Bio-based content of backing by weight (acc. EN 16785) | 100 % | • Total thickness | 160 µm |

Product Assortment

- | | | | |
|--------------------|-------|---------------------|-------|
| • Available colors | white | • Available formats | SPOOL |
|--------------------|-------|---------------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|----------|-------------------------|-----|
| • Elongation at break | 4 % | • Automatic application | yes |
| • Tensile strength | 100 N/cm | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51334>



tesa® 51334

Product Information

Adhesion to Values

- Steel 10 N/cm

Certificates

Sustainability Certificates

- Cepi recyclability laboratory test method version 2 - Standard mill

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51334>