

52117 Steel Master TP

Product Information



Product Description

tesa® Softprint 52117 STM TP is a double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

Product Features

- Foam properties: Highly compressible foam, with superior recovery behavior for excellent print quality. Long lasting recovery characteristic for extended and high speed print runs. Low thickness tolerances for quick print preparation and reduced waste.
- Adhesive properties: High bonding on open side to steel cylinder or sleeve to avoid plate movement. Sufficient
 bonding to plate to avoid edge lifting or plate movement. Non increasing, controlled bonding power for easy
 repositioning and especially for easy demounting of thinner plates. Very cohesive adhesive structure for demounting
 without adhesive residues.
- Additional properties: The structured PP-liner prevents the formation of air pockets when plate mounting. Red color marking indicates the soft foam.
- The soft foam makes this the ideal solution in printing screens and line work.

Application Fields

tesa® Softprint 52117 STM TP is a $380\mu m$ (15 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE foam with film	•	Type of liner	PP
		lamination	•	Total thickness	430 μm
	T (11 :	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			

Type of adhesive tackified acrylic

Properties/Performance Values

•	Color of logo	red	•	Thickness category	380
•	Hardness	soft			

Page 1 of 2 – as of 16/02/24 – en-US



52117 Steel Master TP

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

