

52814 SEC

Product Information



Product Description

Double-coated foam tape

Product Features

- Foam Properties: Low thickness tolerance. Long lasting, constant recovery characteristics
- Adhesive Properties: Low tack surface characteristics. Strong adhesion on both sides. Solvent resistance.
- Additional Properties: Structured PP liner. Logo color indicates foam hardness.

Application Fields

Mounting of 1.14 mm (0.45") and 1.70 mm (0.067") thickness, PET backing, flexographic printing plates onto steel / alu / PU and glassine cylinders and sleeves.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE foam with film	•	Type of liner	PP
		lamination	•	Total thickness	430 μm
•	Type of adhesive	tackified acrylic			

Properties/Performance Values

•	Color of logo	green •	•	Thickness category	380
	Hardness	hard			





52814 SEC

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

